



## Reactor Aluminum Plates

Plate size	Boot size	Plate length in mm	Wheelbase in mm	Toe length* in mm	Heel length** in mm	Plate length in inches	Wheelbase in inches	Plate weight each / pair in ounces	Plate assembly weight*** each / pair in ounces
2	2, 2 1/2	206	124	56	26	8 1/8	4 7/8	5.12 / 10.24	13.60 / 27.20
3	3, 3 1/2	216	134	56	26	8 1/2	5 1/4	5.28 / 10.56	13.76 / 27.52
4	4, 4 1/2	226	144	56	26	8 7/8	5 11/16	5.44 / 10.88	13.92 / 27.84
5	5, 5 1/2	232	150	56	26	9 1/8	5 7/8	5.60 / 11.20	14.08 / 28.16
6	6, 6 1/2	240	156	58	26	9 7/16	6 1/8	5.76 / 11.52	14.24 / 28.48
7	7, 7 1/2	248	162	60	26	9 3/4	6 3/8	5.92 / 11.84	14.40 / 28.80
8	8, 8 1/2	256	168	62	26	10 1/16	6 5/8	6.24 / 12.48	14.72 / 29.44
9	9, 9 1/2	264	174	64	26	10 3/8	6 13/16	6.56 / 13.12	15.04 / 30.08
10	10, 10 1/2	272	180	66	26	10 11/16	7 1/16	6.72 / 13.44	15.20 / 30.40
11	11, 11 1/2	280	186	68	26	11	7 5/16	6.88 / 13.76	15.36 / 30.72
12	12, 12 1/2, 13	288	192	70	26	11 5/16	7 9/16	7.04 / 14.08	15.52 / 31.04

\*Toe length is distance from center of front axle to front end of plate

\*\*Heel length is distance from center of back axle to back end of plate

\*\*\*Plate assembly includes king pins, trucks, cushions, retainers, lock nuts

This chart is a guide - recommendations from the manufacturer. Plate size and mounting can vary for skaters. Skates mounted at Riedell will use this guide unless otherwise specified.